



## Technical Specification

Ranges Available	:	1 Nm, 2 Nm, 3 Nm, 5 Nm, 10 Nm, 20 Nm
Accuracy	:	± 0.5% of F.S.D or ± 2% of reading from 10% to 90%
Display	:	4 ½ Digit LED Backlit Display
Operates On	:	230V A.C. Supply
Jaw Diameter Range	:	20 – 200 mm

## Special Features

- 20-200 mm diameter Bottles or Jars can be tested.
- Choice of different units such as Kgf-m, N-cm, Lb-in.
- Has an accuracy of ± 0.5% of FSD or 2% of reading from 20% to 100% of the rated capacity.
- Peak hold facility.
- Operates on A.C. Main supply.
- It can measure clockwise and counter clockwise values.
- Facility to set upper and lower limit values.
- Audio and visual signal through buzzer and LED indication.
- Facility to tare the initial torque.
- Digital display, clear and easy to read.
- Can be twisted / turned in clock-wise or anti-clockwise directions, and measure torque force.
- Lock up the Maximum Torque value.
- Unit can be switched freely from Nm to Kgf-cm, Lbf-in.

## Optional

- RS-232 facility to hookup with the computer.
- Memory of up to 100 data can be stored.
- Analog output facility is optional.
- Over load alarm.



ISO 9001 : 2008

## Hytech Micro Measurements Pvt. Ltd.

C-24, Shivalik, New Delhi - 110017, India.

T: 91-11-26673108, 26683970

F: 91-11-26683970

E: sales@hytechmicro.com

W: www.hytechmicro.com